

KIEP14 ISM EPDM 70 WRAS

ISM COMPOUNDS

A PRODUCT OF INDUSTRIAL SPARES MANUFACTURING AND TRADING CO

Product description:

KIEP14 ISM EPDM 70 WRAS is a compound crafted to meet WRAS application. It is a terpolymer of ethylene, propylene with incorporation of third non conjugated diene monomer.

Chemistry:

The compound structure consists of ethylene and propylene which makes the saturation excellent, which with addition of diene monomer gives the cure site monomer at the side chain accelerating the cure mechanism without affecting the saturation.

Properties:

The compound covers a wide range of weather properties due to the stronger sigma bonding in main chain and offers better low temperature flexibility than other general purpose rubbers.

Applications:

It is used automotive applications such as weather strip, seals, and in brake systems. It is also used in industrial applications such as O-rings, hoses and gaskets as well as in electrical insulators.

Service temperature:

-55°C to 100°C

Physical properties:

S.No	Description	ASTM Standard	Units	Specification
I	Hardness	D2240	Shore A	70 \pm 5
II	Tensile Strength (Min)	D412	MPa	7
III	Elongation (Min)	D412	%	200
IV	Compression Set (Max) (22hrs@70°C)	D395 Method B	%	25
V	Heat Ageing (70hrs @ 100°C) Hardness Change Tensile Change (Max) Elongation Change (Max)	D573	Shore A % %	\pm 5 \pm 30 - 50

NOTE: 1. The compound has been tested and approved by WRAS

(Water Regulations Advisory Scheme Ltd.)

2. The above compound meets as per ASTM D 2000 M3 BA 707 B13.

The technical datasheets are derived on the basis of the service conditions and end user preference in which the values derived are given over a range of specifications which are cross checked over a variety of trials and approved with the end user conditions and calculated over a prolonged time



Industrial Spares Manufacturing and Trading Co.
No 66 & 77, Perungudi industrial estate,
Perungudi, Chennai – 600096
Tamilnadu, India
Ph: 24961147